



BAKER TANKHEAD, INC. TOOLING & STOCK SIZES

BELOW IS A LIST OF REGULARLY STOCKED HOT AND COLD FORMED CODE AND NON-CODE TANK HEADS.

THE STOCKED SIZES ARE HIGHLIGHTED IN THE CHART, WITH THE LISTED VALUES INDICATING THE MINIMUM THICKNESS FOR OUR CODE HEADS.

NEED A **CUSTOM** BUILD? CONTACT OUR SALES TEAM TODAY AND WE'LL PROVIDE A QUOTE FOR YOUR JOB!

| Cold Formed ASME 2:1 Elliptical Heads | | | | | | Non-code STD F&D Heads | | | |
|---------------------------------------|-------|-------|-------|-------|-------|------------------------|------|------|-----|
| OD | 1/4 | 3/8 | 1/2 | 5/8 | 3/4 | OD | 10GA | 3/16 | 1/4 |
| 30 | 0.204 | | | | | 20 | | X | |
| | | | | | | 24 | | | X |
| 36 | 0.204 | | | | | 26 | X | | |
| | | | | | | 30 | X | X | X |
| 48 | 0.204 | | | | | 36 | X | X | X |
| | | | | | | 42 | | X | X |
| 60 | | 0.312 | 0.417 | | | 48 | | X | X |
| | | | | | | 54 | | | X |
| 72 | | 0.312 | 0.417 | 0.523 | | 60 | | | X |
| | | | | | | 66 | | | X |
| 96 | 0.204 | 0.312 | 0.417 | 0.523 | 0.629 | 72 | | | X |
| | | | | | | 76 | | | X |

| HP & CP OD ASME 2:1 Elliptical Heads | | | | | | | | | | | | | | | | | | |
|--------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| OD | 3/16 | 1/4 | 5/16 | 3/8 | 1/2 | 5/8 | 3/4 | 7/8 | 1 | 1 1/8 | 1 1/4 | 1 3/8 | 1 1/2 | 1 5/8 | 1 3/4 | 2 | 2 1/2 | |
| 6 5/8 | | | 0.278 | | | | | | | | | | | | | | | |
| 8 5/8 | | | 0.297 | 0.343 | 0.429 | 0.554 | | | | | | | | | | | | |
| 10 3/4 | 0.171 | 0.227 | 0.281 | 0.340 | 0.451 | 0.555 | | | 0.875 | | | | | | | | | |
| 12 3/4 | 0.163 | 0.229 | 0.279 | 0.348 | 0.446 | 0.579 | 0.682 | 0.780 | 0.909 | | | | | | | | | |
| 14 | | | | 0.351 | 0.473 | 0.562 | 0.671 | | 0.903 | | 1.105 | | | | | | | |
| 16 | | 0.228 | | 0.341 | 0.452 | 0.571 | 0.698 | 0.780 | 0.911 | 1.033 | 1.120 | | | | | | | 1.947 |
| 18 | | | | 0.344 | 0.463 | 0.593 | 0.703 | 0.798 | 0.931 | | 1.155 | | | | | | 1.831 | |
| 20 | | | 0.283 | 0.341 | 0.467 | 0.583 | 0.701 | 0.812 | 0.923 | 1.066 | 1.187 | | | | | | | |
| 22 | | | | 0.341 | 0.468 | | | | | | | | | | | | | |
| 24 | | 0.188 | 0.272 | 0.342 | 0.461 | 0.579 | 0.701 | 0.822 | 0.940 | 1.059 | 1.189 | | | 1.500 | | | 1.829 | |
| 26 | | | | 0.341 | 0.467 | 0.579 | | | | | | | | | | | | |
| 28 | | | | 0.345 | 0.464 | 0.596 | 0.712 | | 0.939 | | | | | | | | | |
| 30 | | | | 0.333 | 0.465 | 0.587 | 0.708 | 0.836 | 0.939 | 1.071 | 1.185 | 1.307 | | | | 1.663 | | |
| 32 | | | | | 0.465 | | 0.715 | | | | | | | | | | | |
| 34 | | | | | | | 0.701 | | | | | | | | | | | |
| 36 | | | | 0.334 | 0.455 | 0.588 | 0.662 | 0.838 | 0.934 | 1.072 | | 1.299 | 1.423 | | 1.665 | | | |
| 42 | | | | 0.344 | 0.465 | 0.571 | | | | | | | | | | | | |
| 48 | | | | 0.333 | 0.465 | 0.559 | 0.717 | 0.840 | 0.940 | 1.086 | | | 1.449 | | 1.677 | 1.925 | | |

| HP ID ASME 2:1 Elliptical Heads | | | | | | | | | | | | | | | | | |
|---------------------------------|------|-----|------|-----|-----|-----|-----|-------|------|-------|-------|-------|-------|-------|-------|---|-------|
| ID | 3/16 | 1/4 | 5/16 | 3/8 | 1/2 | 5/8 | 3/4 | 7/8 | 1 | 1 1/8 | 1 1/4 | 1 3/8 | 1 1/2 | 1 5/8 | 1 3/4 | 2 | 2 1/2 |
| 30 | | | | | | | | 0.833 | | | 1.201 | | | | | | |
| 36 | | | | | | | | | .973 | | | | | | | | |

CONTACT OUR SALES TEAM TODAY FOR YOUR CUSTOM QUOTE. 817-232-8030 WWW.BAKERTANKHEAD.COM

EXCEPTIONAL QUALITY. RAPID TURNAROUND. UNMATCHED SERVICE.
SHAPING THE WORLD ONE TANK HEAD AT A TIME.